

GUIDE

TRAILER & TOWING



THINGS YOU NEED & THINGS TO KNOW!

1

BALL MOUNT

Connects your vehicle to the trailer ball

MAKE SURE TO KNOW:

- **Receiver size** on your vehicle
- **Rise or drop** ball mount to keep your trailer level
- **Shank length** to provide clearance when turning
- **Hole size** must match your trailer ball shank

**2**

TRAILER BALL

Connects directly to your trailer coupler

MAKE SURE TO MATCH:

- **Ball Diameter** must match your coupler exactly
- **Shank diameter** must match the ball mount hole
- **Weight rating** must meet or exceed your trailer weight

**3**

TRAILER COUPLER

Attaches your trailer to the trailer ball

MAKE SURE TO CHECK FOR:

- **Correct trailer ball size**
- **Weight rating** must handle your fully loaded trailer
- **Proper fit & latch** should close securely with no looseness



YOUR SAFE TOWING LIMIT = YOUR LOWEST-RATED COMPONENT

- GTW (Gross Trailer Weight) = total loaded trailer weight
- Tongue Weight (TW) = downward force on hitch → Should be 10–15% of GTW

MAKE SURE YOU HAVE THE RIGHT PARTS & THE RIGHT FIT!



SCAN THE QR CODE FOR MORE INFORMATION
ON MEASUREMENTS AND TOWING SETUP.

